




Cherne's Gripper plugs can be used in a variety of applications including DWV (drain, waste and vent) testing and stack testing. End-of-the-pipe design won't fall in, whereas the Inside-of-the-pipe design allows you to locate the plug inside the pipe as far as you need. Time tested, the Gripper® remains one of the most popular mechanical plugs on the market.

Original Gripper® Plug Features:


- Ideal for sewer testing and long-term applications
- Made with glass-reinforced ABS plastic
- End-of-pipe design seals only at the end of a pipe
- Inside-of-pipe design seals inside pipe as far as needed

Equipped with:

- Easy-to-install extra-large wing nut
- Natural rubber o-ring



End-of-pipe Gripper® plug



Inside-of-pipe Gripper® plug

Part #	Nominal Size	Size Usage Range		Maximum Allowable Back Pressure		Product Specifications			
		Minimum Diameter	Maximum Diameter	Air Pressure PSI*	Head Pressure (Feet of Head)	Plug Size		Product Weight	Carton Quantity
						Diameter	Length		
Original Gripper® Plugs: End-of-Pipe									
270210	1½" (40 mm)	1.48" (39 mm)	1.65" (42 mm)	17 (1,2 bar)	40 (12 M)	1.46" (38.4 mm)	1.75" (44.5 mm)	.13 lb (.06 kg)	10
270229	2" (50 mm)	1.9" (49 mm)	2.17" (55 mm)	17 (1,2 bar)	40 (12 M)	1.89" (47.8 mm)	1.87" (47.5 mm)	.19 lb (.09 kg)	10
270237	3" (75 mm)	2.8" (71 mm)	3.1" (79 mm)	17 (1,2 bar)	40 (12 M)	2.76" (70.1 mm)	2.5" (63.5 mm)	.375 lb (.16 kg)	10
270245	4" (100 mm)	3.8" (96 mm)	4.06" (103 mm)	17 (1,2 bar)	40 (12 M)	3.76" (95.5 mm)	2.5" (63.5 mm)	.5 lb (.23 kg)	10
270261	6" (150 mm)	5.77" (147 mm)	6.08" (154 mm)	17 (1,2 bar)	40 (12 M)	5.75" (145.9 mm)	3.75" (95.3 mm)	2.5 lbs (1.14 kg)	5
270270	8" (200 mm)	7.7" (196 mm)	8.03" (204 mm)	17 (1,2 bar)	40 (12 M)	7.75" (196.7 mm)	3.75" (95.3 mm)	3 lbs (41.36 kg)	1
Original Gripper® Plugs: Inside-of-Pipe									
270296	4" (100 mm)	3.8" (96 mm)	4.06" (103 mm)	17 (1,2 bar)	40 (12 M)	3.76" (95.5 mm)	2.5" (63.5 mm)	.5 lb (.23 kg)	10
270253	6" (150 mm)	5.77" (147 mm)	6.08" (154 mm)	17 (1,2 bar)	40 (12 M)	5.75" (145.9 mm)	3.75" (95.3 mm)	2.5 lbs (1.14 kg)	5
270288	8" (200 mm)	7.7" (196 mm)	8.03" (204 mm)	17 (1,2 bar)	40 (12 M)	7.75" (196.7 mm)	3.75" (95.3 mm)	3 lbs (41.36 kg)	1

* Always block plugs when conducting air tests!